



SAFETY DATA SHEET

DATE: JAN 01 2018

Number: 1

1. PRODUCT AND COMPANY IDENTIFICATION

Product name EVOpaint - REPAINT Flat, REPAINT Eggshell, DRYWALL Flat, DRYWALL Eggshell.
Product code 500A, 500B, 300A, 300B
Product class Water Thinned Paint
Color All

Manufacturer

Wheelhouse Coatings Inc.
402 Mulock Dr. Unit #5
Newmarket, Ontario, L3Y 9B8
Canada
Phone: 888-470-1320
www.evopaints.com

Emergency Telephone Number(s)

EVOpaint: 888-470-1320

2. COMPOSITION INFORMATION ON COMPONENTS

HAZARDOUS COMPONENTS

CHEMICAL NAME	CAS #	WEIGHT %
Titanium Dioxide	13463-67-7	10 to 30
Diatomaceous Earth	1344-28-1	1 to 5
Propylene Glycol	57-55-6	1 to 5

3. HAZARDS IDENTIFICATION

Emergency Overview

Vapors may be irritating to the eyes, nose, throat and lungs. May cause skin irritation and/or dermatitis

Appearance Liquid

Odor little to no odor

Potential Health Effects

Principle Routes of Exposure

Eye contact, skin contact and inhalation.

Acute Effects

Eyes	May cause mild irritation
Skin	May cause mild skin irritation
Inhalation	May cause mild irritation of the respiratory tract.
Ingestion	May cause nausea, vomiting and diarrhea.

Chronic Effects

Prolonged contact may cause allergic reactions in very susceptible individuals.

See Section 11 for further Toxicological information.

Aggravated Medical Conditions None known

HMIS Health: 1 Flamability: 0 Reactivity: 0 PPE:-

HMIS Legend

- 0 - Minimal Hazard
- 1 - Slight Hazard
- 2 - Moderate Hazard
- 3 - Serious Hazard
- 4 - Severe Hazard
- * - Chronic Hazard
- X - Consult your supervisor or S.O.P. for special handling instructions

Note: The PPE rating has intentionally been left blank. Choose appropriate PPE that will protect employees from the hazards the material will present under normal conditions of use.

Caution: HMIS ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risk, and 4 representing significant hazards or risks. Although HMIS ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer has chosen to provide them. HMIS ratings are to be used only in conjunction with a fully implemented HMIS program by workers who have received appropriate HMIS training. HMIS is a registered trade and service mark of the NPCA. HMIS materials may be purchased exclusively from J.J. Keller (800) 327-6868

4. FIRST AID MEASURES

General	No hazards that require special first aid measures
Eyes	Rinse thoroughly with plenty of water for at least 15 mins. Consult physician.
Skin	Wash off thoroughly right away with soap & water
Inhalation	Move to fresh air. If symptoms continue call physician.
Ingestion	Rinse mouth thoroughly with water and drink plenty of water and if necessary consult physician
Note to Physician	Treat symptomatically.

5. FIRE FIGHTING MEASURES

Suitable Extinguishing Media Use extinguishing measures that are appropriate to local circumstances and the surrounding environment

Protective Equipment And Precautions For Firefighters

As in any fire, wear self-contained breathing apparatus pressure demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

Specific Hazards Arising From Chemical Closed containers may rupture if exposed to fire or extreme heat.

Sensitivity To Mechanical Impact No

Sensitivity To Static Discharge No

Flash Point Data

Flash Point (° F) Not applicable

Flash Point (° C) Not applicable

Flash Point Method Not applicable

Fammability Limits In Air

Upper Explosion Limits Not Applicable

Lower Explosion Limits Not Applicable

NFPA **Health** 1 **Flammability** 0 **Instability** 0 **Special** n/a

NFPA Legend

0 - Not Hazardous

1 - Slightly

2 - Moderate

3 - High

4 - Severe

6. ACCIDENTAL RELEASE MEASURES

Methods of Clean	Soak up with inert absorbent material, collect and place into suitable containers
Environmental Precautions	Attempt to prevent further spillage if safe to do so.
Personal Precautions	Avoid contact with eyes, skin and clothing. Ensure adequate ventilation.

7. HANDLING AND STORAGE

Handling	Avoid contact with eyes, skin and clothing. Handle in well ventilated area Avoid breathing vapours, spray or sanding dust. If insufficient ventilation wear suitable respiratory equipment.
Storage	Keep container well sealed and keep out of reach of children.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Limits

	Titanium Dioxide	Diatomaceous earth	Propylene glycol
ACGIH	10 mg/m ³ - TWA	N/E	N/E
Alberta	10 mg/m ³ - TWA	10 mg/m ³ - TWA 3 mg/m ³ - TWA	N/E
British Columbia	10 mg/m ³ - TWA 3 mg/m ³ - TWA	1.5 mg/m ³ - TWA 4 mg/m ³ - TWA	N/E
Ontario	10mg/m ³ - TWAEV	10mg/m ³ - TWAEV containing no asbestos and less than 1% crystalline silica 3 mg/m ³ - TWAEV containing no asbestos and less than 1% crystalline silica	10 mg/m ³ - TWAEV for assessing the visibility in a work environment 155 mg/m ³ - TWAEV 50ppm - TWAEV
Quebec	10 mg/m ³ - TWAEV	6 mg/m ³ - TWAEV	N/E

Legend

ACGIH	American Conference of Governmental Industrial Hygienists
Alberta	Alberta Occupational Exposure Limits
British Columbia	British Columbia Occupational Exposure Limits
Ontario	Ontario Occupational Exposure Limits
Quebec	Quebec Occupational Exposure Limits
N/E	Not Established

Engineering Measures	Ensure adequate ventilation, especially in confined areas
Eye / Face protection	Safety Glasses
Skin protection	Protective gloves and clothing
Respiratory protection	In case of insufficient ventilation wear appropriate respiratory Equipment
Hygiene measures	Avoid contact with eyes, skin and clothing. Wash thoroughly after handling

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Liquid
Odor	Little or no odor
Density (Lbs/Gal)	11.5 - 12.3
Specific Gravity	1.5 - 1.6
Ph	8 - 9.7
Viscosity (centistokes)	Not available
Evaporation Rate	Not available
Vapor Pressure	Not available
Vapor Density	Not available
Wt % Solids	65 - 75
Wt. % Volatile	25 - 35
VOC (g/L)	< 100
Boiling Point (° F)	212
Boiling Point (° C)	100
Freezing Point (° F)	32
Freezing point (° C)	0
Flash Point (° F)	Not applicable
Flash Point (° C)	Not applicable
Flash Point Method	Not applicable
Upper Explosion Limit	Not available
Lower Explosion Limit	Not available

10. STABILITY AND REACTIVITY

Chemical Stability	Stable under normal conditions
Conditions To Avoid	Prevent from freezing
Incompatible Material	No materials to be specially mentioned
Hazardous Decomposition Products	None under normal use

11. TOXICOLOGICAL INFORMATION

Acute Toxicity

Product No information available

Component

Titanium Dioxide

LD50 ORAL RAT: >10000 mg/kg
 LD50 DERMAL RABBIT: >10000 mg/m3
 LC50 INHALATION (DUST): > 6.82 mg/L (RAT, 4 hr)

Propylene Glycol

LD50 ORAL RAT: 20000 mg/kg
 LD50 DERMAL RABBIT: 20800 mg/kg

Chronic Toxicity

Carcinogenicity

The information below indicates whether each agency has list any ingredient as a carcinogen

Chemical name	ACGIH	IARC	NTP	OSHA
Titanium Dioxide		2B - Possible Human Carcinogen		Listed

Legend

- ACGIH** American Conference of Governmental Industrial Hygienists
- IARC** International Agency for Research on Cancer
- NTP** National Toxicity Program
- OSHA** Occupational Safety and Health Administration

12. ECOLOGICAL INFORMATION

Eotoxicity Effects

Product

Acute Toxicity To Fish

No information available

Acute Toxicity To Aquatic Invertebrates

No information available

Acute Toxicity To Aquatic Plants

No information available

Component

Acute Toxicity to Fish

Titanium Dioxide

LC50: >1000 mg/L (Flathead Minnow - 96hr)

Propylene Glycol

LC50: 710 mg/L (Flathead Minnow - 96 hr)

Acute Toxicity to Aquatic Invertebrates

Propylene Glycol

EC50: >10000 mg/L (Daphnia Magna - 24 hr)

Acute Toxicity to Aquatic Plants

No information available

13. DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD

Dispose of in accordance with Federal, state, provincial and local regulations. Dry, empty containers may be recycled in a recycling program. Local requirements may vary, consult your local authorities for proper disposal.

14. TRANSPORT INFORMATION

TDG Not regulated

ICAO / IATA Not regulated

IMDG / IMO Not regulated

15. REGULATORY INFORMATION

International Inventories

United States TSCA Yes - All components are listed or exempt
Canada DSL Yes - All components are listed or exempt

National Pollutant Release Inventory

NPRI parts 1-4

This product contains the following parts 1-4 NPRI chemicals
 N/A

This product may contain trace amounts of (other) NPRI parts 1-4 reportable chemicals.
 Contact the preparer for more information.
 N/A

NPRI Part 5

This product contains the following NPRI Part 5 Chemicals
 N/A

This product may contain trace amounts of (other) NPRI Part 5 reportable chemicals.
 the preparer for more information
 N/A

WHMIS Regulatory Status

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

WHMIS Hazard Class

DA2 Very toxic material



16. OTHER INFORMATION

WARNING! If you scrape, sand, or remove paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by logging onto :
 HEALTH Canada @ http://www.hc-sc-gc.ca/iyh-vsv/prod/paint-peinture_e.html.

Prepared date: JAN 01 2018

Disclaimer

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, provincial, local laws and regulations.

End of SDS